

Ensure Peak Performance

The Artista CR805 Retransfer Printer features specialized print ribbons, retransfer film, laminates, and other supplies, all specifically designed for optimal performance combined with our Entrust

2 -001 2 -001 2 -002 C	I E N BE	DE IP ION	(IELD
21 1-002	12.11.1.277.12.1		
N/A N/A	2 -001	الأخياس الأخياس المتعارض المتع	N/A
0 3 -001 C	21 1-002	\$\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	N/A
1233 - 001	002	S,	N/A
12 2 - 001 G	0 3 -001	\$ ()(l, ,	N/A
N/A N/A	1233 -001	C L. , G. , . (, 12)	N/A
2 1 -001 P Ç G () N/A 1 10-01 D G L 10 , , 300 1 10-02 D G L 10 , , 300 1 10-05 D G L 10 , 300 1 0,2-001 D G O , L 10 , 300 1 0,2-301 D G O , L 10 , 300 1 0,2-302 D G O , G L 10 , 300 2 0, -015 F, C M , M 1,000 2 0, -003 F, C G , M , 1,000 2 0, -002 F, C B , 1,000 2 0, -002 F, C B , 1,000	12 2 -001	Ç ,	N/A
1 10- 01	1010 -001	Ç L	N/A
1 10- 01 D G L 1, 10 10 10 10 10 10 10 10 10 10 10 10 10	2 1 -001	P ₁ ,	N/A
1 10- 02		Operation by made on a proper	
1 10- 03 D. G. L 10	1 10- 01	Q G L ,. ,1.0 ,, , ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	300
1 0, 2-001 D. G. O. A. L. A.	1 10- 02	Q G L 3. 31.0 9.3 3.4 2 2 3 2 2	300
1 0, 2-301 D G O G L G L G G G G G G G G G G G G G G	1 10- 03	Q G L 3. 31.0 3.3 3.3 3.3	300
1 0, 2-002 D G O G L , , , 10 , , ,	1 0 2-001	Q G O ; , L ;. ,1.0 ,, , ,»	300
1 0, 2-002 D G O G L , , , 1.0 , ,	1 0 2-301		300
O 1,000 2 0, -013 F., C M 3. 1,000 2 0, -003 F., C G, M 3. 1,000 2 0, -033 F., C C M 3. 1,000 2 0, -002 F., C B 1,000 2 0, -02 F., C B 1,000	1 0, 2-002		300
2 0, -013 , F., C , M 1,000 2 0, -003 , F., C G, M 1,000 2 0, -033 , F., C C. M 1,000 2 0, -002 , F., C B 1,000 2 0, -02 , F., C 0	1 0, 2-302		300
2 0, -013 , F., C , M ; 1,000 2 0, -003 , F., C G, M ; 1,000 2 0, -033 , F., C C. M ; 1,000 2 0, -002 , F., C B 1,000 2 0, -02 , F., C 0		Opening house years I proceed the company of	
2 0, -033 F., C C M ,, 2 0, -002 F., C B , 2 0, -02 F., C O	2 0 -013		1,000
2 0, -002	2 0, -003	, F., C G., M ,,	1,000
2 0, -02 F., C ,	2 0、-033	, F., C C. M ,,	1,000
	2 0、-002	, F., C B, ,	1,000
2 Q -O , F., C G	2 0、-02	, F., C	0
	2 0 -0	, F., C	1,000



EAE	DE IP ION	OP I AL E DE AIL
СМ К	E _{**} · ** · · · · · · · · · · · · · · · ·	Depose = Epops of the property
CM K-K	E, .,	D E
CM KP-KR	E,	D + 1 E + 1
FCM P-KP	E, ,	D


C - Cyan M = Magenta Y = Yellow K = Black P = Primer F = UV fluorescent I = Inhibitor

Inhibitor panel is used for mag stripe or signature panels.

Ensuring the right fit when it comes to card life expectations is critical. The Artista CR805 has simple solutions to easily increase card durability for your programs and stand up to life's demands.

- Standalone printers can extend card durability simply by applying a second layer of the retransfer film during printing application
- Printers with the inline lamination module include optimal card durability application capabilities utilizing lamination supplies

With Entrust solutions and our industry expertise on your side, you can print quality, vibrant, lasting cards.



^{*}Primerless color ribbons and retransfer film available exclusively for the access control and government markets. Requires Firmware R4.10.2-13 (or higher). Unique formulation requires primerless color ribbons to be used in conjunction with retransfer film formulated for primerless ribbons. (513107-xxx color ribbons to be used with 513157-xxx retransfer film.) For use with PVC cards. Use with polycarbonate (PC) cards not recommended and requires testing.

^{**}Color ribbons with a primer panel to be used in conjunction with retransfer film formulated for color ribbons with primer panel. (513382-xxx color ribbons to be used with 513402-xxx retransfer film.)

##